

# Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/03/2024

## 1 Identification

- **Product Identifier**
- **Trade Name: Uberseal™ 3.1**
- **Relevant identified uses of the substance or mixture and uses advised against:**  
No further relevant information available.
- **Product Description:** Hybrid Elastomeric Sealant / Adhesive
- **Details of the Supplier of the Safety Data Sheet:**
- **Manufacturer/Supplier:**  
UberTile® A division of the Rudiger Group Inc.  
10330-117 Ave  
Grande Prairie, Ab, T8V-7S5  
Phone: 877-759-5755
- **Emergency telephone number:**  
CHEMTREC: Canada/USA- 1-800-424-9300  
International - (703) 527-3887

## 2 Hazard(s) Identification

- **Classification of the substance or mixture:**



Health hazard

- |          |  |
|----------|--|
| Carc. 1A | H350 May cause cancer.                         |
| Repr. 1B | H360 May damage fertility or the unborn child. |



- |                   |   |
|-------------------|---|
| Skin Sens. 1      | H317 May cause an allergic skin reaction.               |
| Eye Irrit. 2B     | H320 Causes eye irritation.                             |
| Aquatic Acute 2   | H401 Toxic to aquatic life.                             |
| Aquatic Chronic 3 | H412 Harmful to aquatic life with long lasting effects. |

- **Label elements:**
- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**



GHS07



GHS08

- **Signal word:** Danger
- **Hazard-determining components of labeling:**  
Titanium Dioxide  
Dibutyltin bis(acetylacetonate)  
Quartz (SiO<sub>2</sub>)  
N-(3-(trimethoxysilyl)propyl)ethylenediamine
- **Hazard statements:**  
H320 Causes eye irritation.  
H317 May cause an allergic skin reaction.

- H350 May cause cancer.
- H360 May damage fertility or the unborn child.
- H401 Toxic to aquatic life.
- H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements:**

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302+P352 If on skin: Wash with plenty of water.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 If exposed or concerned : Get medical advice/attention.
- P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Unknown acute toxicity:**

This value refers to knowledge of known, established toxicological or ecotoxicological values.

- **Classification system:** NFPA/HMIS Definitions: 0-Least, 1 -Slight, 2-Moderate, 3-High, 4-Extreme
- **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



- **Hazard(s) not otherwise classified (HNOC):** None known

### 3 Composition/Information on Ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of substances listed below with non-hazardous additions

· **Dangerous Components:**

|                                    |  |        |
|------------------------------------|--|--------|
| CAS: 471-34-1<br>RTECS: EV 9580000 | Calcium Carbonate  | 25-50% |
| CAS: 1317-65-3                     | Natural limestone  | 25-50% |
| CAS: 68515-49-1                    | Diisodecyl Phthalate<br>Aquatic Acute 1, H400; Eye Irrit. 2B, H320 | 15-35% |

(Contd. on page 3)

|                                      |   |       |
|--------------------------------------|---|-------|
| CAS: 57-11-4<br>RTECS: WI 2800000    | Stearic Acid, pure<br>⚠ Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320   | 5-10% |
| CAS: 13463-67-7                      | Titanium Dioxide<br>⚠ Carc. 2, H351   | 2-12% |
| CAS: 2768-02-7                       | Trimethoxyvinylsilane<br>⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 4, H332   | ≤2.5% |
| CAS: 67-56-1<br>RTECS: PC 1400000    | Methanol<br>⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; ⚠ STOT SE 1, H370           | ≤2.5% |
| CAS: 1760-24-3<br>RTECS: KV 7400000  | N-(3-(trimethoxysilyl)propyl)ethylenediamine<br>⚠ Skin Corr. 1A, H314; Eye Dam. 1, H318; ⚠ Skin Sens. 1, H317               | ≤2.5% |
| CAS: 25973-55-1                      | 2-(2H-benzotriazol -2-yl)-4,6-di-tert-pentylpheno l   | ≤2.5% |
| CAS: 14808-60-7<br>RTECS: VV 7330000 | Quartz (SiO <sub>2</sub> )<br>⚠ Carc. 1A, H350; STOT RE 1, H372; ⚠ Acute Tox. 4, H332; STOT SE 3, H335; Eye Irrit. 2B, H320 | ≤2.5% |

• **Additional information:**

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

#### 4 First-Aid Measures

• **Description of first aid measures**

• **General information:**

Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.

• **After inhalation:**

Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Get immediate medical attention.

• **After skin contact:**

Immediately wash skin with soap and plenty of water for at least 15 minutes.  
Remove contaminated clothing and wash before reuse.  
Get medical attention if symptoms occur.

• **After eye contact:**

If easy to do so, remove contact lenses if worn.  
Hold eyelids apart and flush eyes with plenty of water for at least 20 minutes.  
Seek medical treatment.

• **After swallowing:**

Do not induce vomiting.  
If conscious, give no more than two glasses of water.  
Seek medical treatment.

• **Information for doctor**

• **Most important symptoms and effects, both acute and delayed:**

May cause an allergic skin reaction. Prolonged exposure may cause chronic effects.

• **Indication of any immediate medical attention and special treatment needed:** Treat symptomatically.

#### 5 Fire-Fighting Measures

• **Extinguishing media**

• **Suitable extinguishing agents:**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

• **For safety reasons unsuitable extinguishing agents:** Water with full jet

- **Special hazards arising from the substance or mixture:**  
Hazardous decomposition products include: carbon dioxide, carbon monoxide and incompletely burnt hydrocarbons.
- **Advice for firefighters**
- **Special protective equipment for firefighters:**  
As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.
- **Additional information:** Cool fire exposed containers with water.

## 6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures:**  
Ensure adequate ventilation.  
Wear protective equipment. Keep unprotected persons away.  
Avoid contact with skin, eyes and clothing.  
Do not breathe vapor.  
Product is slippery when spilled.
- **Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/surface or ground water.
- **Methods and material for containment and cleaning up:**  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents  
Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.
- **Reference to other sections:**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

• **PAC-1:**

|            |  |                         |
|------------|--|-------------------------|
| 471-34-1   | Calcium Carbonate                            | 45 mg/m <sup>3</sup>    |
| 57-11-4    | Stearic Acid, pure                           | 14 mg/m <sup>3</sup>    |
| 13463-67-7 | Titanium Dioxide                             | 30 mg/m <sup>3</sup>    |
| 2768-02-7  | Trimethoxyvinylsilane                        | 9.5 ppm                 |
| 67-56-1    | Methanol                                     | 530 ppm                 |
| 1760-24-3  | N-(3-(trimethoxysilyl)propyl)ethylenediamine | 23 mg/m <sup>3</sup>    |
| 14808-60-7 | Quartz (SiO <sub>2</sub> )                   | 0.075 mg/m <sup>3</sup> |

• **PAC-2:**

|            |  |                       |
|------------|--|-----------------------|
| 471-34-1   | Calcium Carbonate                            | 210 mg/m <sup>3</sup> |
| 57-11-4    | Stearic Acid, pure                           | 150 mg/m <sup>3</sup> |
| 13463-67-7 | Titanium Dioxide                             | 330 mg/m <sup>3</sup> |
| 2768-02-7  | Trimethoxyvinylsilane                        | 100 ppm               |
| 67-56-1    | Methanol                                     | 2,100 ppm             |
| 1760-24-3  | N-(3-(trimethoxysilyl)propyl)ethylenediamine | 250 mg/m <sup>3</sup> |
| 14808-60-7 | Quartz (SiO <sub>2</sub> )                   | 33 mg/m <sup>3</sup>  |

• **PAC-3:**

|          |                   |                         |
|----------|-------------------|-------------------------|
| 471-34-1 | Calcium Carbonate | 1,300 mg/m <sup>3</sup> |
|----------|-------------------|-------------------------|

(Contd. on page 5)

|            |  |                         |
|------------|--|-------------------------|
| 57-11-4    | Stearic Acid, pure                           | 910 mg/m <sup>3</sup>   |
| 13463-67-7 | Titanium Dioxide                             | 2,000 mg/m <sup>3</sup> |
| 2768-02-7  | Trimethoxyvinylsilane                        | 120 ppm                 |
| 67-56-1    | Methanol                                     | 7200* ppm               |
| 1760-24-3  | N-(3-(trimethoxysilyl)propyl)ethylenediamine | 1,500 mg/m <sup>3</sup> |
| 14808-60-7 | Quartz (SiO <sub>2</sub> )                   | 200 mg/m <sup>3</sup>   |

### 7 Handling and Storage

- **Handling**
- **Precautions for safe handling:**  
 Ensure good ventilation/exhaustion at the workplace.  
 Avoid contact with skin, eyes and clothing  
 Avoid breathing fume/gas/mist/vapors/spray.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:**  
 Store in a cool, dry place.  
 Store in a well ventilated place.  
 Store in the original container.  
 Protect from moisture.
- **Information about storage in one common storage facility:** See Section 10 (Incompatible materials)
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s):** No further relevant information available.

### 8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters:**
- **Components with occupational exposure limits:**  
 The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
 At this time, the other constituents have no known exposure limits.

|                             |   |
|-----------------------------|---|
| 471-34-1 Calcium Carbonate  |   |
| PEL                         | Long-term value: 15* 5** mg/m <sup>3</sup><br>*total dust **respirable fraction                   |
| REL                         | Long-term value: 10* 5** mg/m <sup>3</sup><br>*total dust **respirable fraction                   |
| TLV                         | TLV withdrawn   |
| 1317-65-3 Natural limestone |   |
| NIOSH                       | Short-term value: 5 mg/m <sup>3</sup><br>Long-term value: 10 mg/m <sup>3</sup>                    |
| NIOSH TWA                   | Short-term value: 5 mg/m <sup>3</sup><br>Long-term value: 10 mg/m <sup>3</sup><br>respirable dust |

(Contd. on page 6)

|                                       |  |
|---------------------------------------|--|
| OSHA                                  | Short-term value: 5 mg/m <sup>3</sup><br>Long-term value: 15 mg/m <sup>3</sup>                                     |
| OSHA TWA                              | Short-term value: 5 mg/m <sup>3</sup><br>Long-term value: 15 mg/m <sup>3</sup><br>espirable fraction               |
| 68515-49-1 Diisodecyl Phthalate       |  |
| OSHA PEL                              | Short-term value: 5 mg/m <sup>3</sup>  |
| 67-56-1 Methanol                      |  |
| REL                                   | Long-term value: 260 mg/m <sup>3</sup> , 200 ppm   |
| REL                                   | Short-term value: 325 mg/m <sup>3</sup> , 250 ppm<br>Long-term value: 260 mg/m <sup>3</sup> , 200 ppm<br>Skin      |
| TLV                                   | Short-term value: 328 mg/m <sup>3</sup> , 250 ppm<br>Long-term value: 262 mg/m <sup>3</sup> , 200 ppm<br>Skin; BEI |
| 14808-60-7 Quartz (SiO <sub>2</sub> ) |  |
| REL                                   | Long-term value: 0.05* mg/m <sup>3</sup><br>*resp. dust; 30mg/m <sup>3</sup> /%SiO <sub>2</sub> +2                 |
| REL                                   | Long-term value: 0.05* mg/m <sup>3</sup><br>*respirable dust; See Pocket Guide App. A                              |
| TLV                                   | Long-term value: 0.025* mg/m <sup>3</sup><br>*as respirable fraction   |

• **Ingredients with biological limit values:**

|                  |  |
|------------------|--|
| 67-56-1 Methanol |  |
| BEI              | 15 mg/L<br>urine<br>end of shift<br>Methanol (background, nonspecific) |

• **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

• **Exposure controls:**

• **Personal protective equipment**

• **General protective and hygienic measures:**

- Do not smoke around this product.
- Do not eat or drink while handling product.
- The usual precautionary measures for handling chemicals should be followed.
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing and wash before reuse.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.

• **Breathing equipment:**



NIOSH/OSHA or EN approved respiratory protection is recommended for use in airborne concentrations exceeding exposure limits.

· **Protection of hands:**



Protective gloves

- **Material of gloves:** Any liquid-tight rubber or vinyl rubber protective gloves.
- **Penetration time of glove material:**  
The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.
- **Eye protection:**



Tightly sealed goggles

- **Limitation and supervision of exposure into the environment:**  
Keep away from drains, surface and ground waters.  
Avoid release into the environment.

## 9 Physical and Chemical Properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

- **Form:** Paste
- **Color:** White
- **Odour:** Slight
- **Odor threshold:** Not determined.

- **pH-value:** Not applicable.

· **Change in condition**

- **Melting point/Melting range:** Not determined.
- **Boiling point/Boiling range:**  $\geq 250\text{ °C}$  (  $\geq 482\text{ °F}$ )

- **Flash point:**  $> 200\text{ °C}$  ( $> 392\text{ °F}$ ) (ISO 2592)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:**  $\geq 395\text{ °C}$  (  $\geq 743\text{ °F}$ )

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not self-igniting.

- **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

- **Lower:** Not determined.
- **Upper:** Not determined.

- **Vapor pressure @ 20 °C (68 °F):**  $< 1.0\text{ hPa}$  ( $< 0.8\text{ mm Hg}$ )

- **Density @ 20 °C (68 °F):**  $1.66\text{ g/cm}^3$  (13.8527 lbs/gal)

- **Relative density:** Not determined.

- **Vapor density:**  $> 1$  (Air=1)

- **Evaporation rate:**  $< 1$  (n-Butyl Acetate =1)

(Contd. on page 8)

- **Solubility in / Miscibility with:**
  - Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - Dynamic:** Not determined.
  - Kinematic:** Not determined.
- **Solvent content:**
  - VOC content:** 18 g/l
- **Other information:** No further relevant information available.

## 10 Stability and Reactivity

- **Reactivity:** Stable under normal conditions.
- **Chemical stability:** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:**  
Thermal decomposition will result in carbon monoxide, carbon dioxide and or low molecular weight hydrocarbons.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** Avoid heat, flames and sparks. Avoid contact with incompatible materials.
- **Incompatible materials:**
  - Strong acids
  - Strong oxidizing agents.
- **Hazardous decomposition products:**  
Upon decomposition, this product emits carbon monoxide, carbon dioxide and or low molecular weight hydrocarbons.

## 11 Toxicological Information

- **Information on toxicological effects:**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**

|                             |               |                        |
|-----------------------------|---------------|------------------------|
| 471-34-1 Calcium Carbonate  |               |                        |
| Oral                        | LD50          | 6,450 mg/kg (Rat)      |
| 1317-65-3 Natural limestone |               |                        |
| Oral                        | LD50          | 6,450 mg/kg (Rat)      |
| 57-11-4 Stearic Acid, pure  |               |                        |
| Dermal                      | LD50          | >5,000 mg/kg (Rabbit)  |
| 13463-67-7 Titanium Dioxide |               |                        |
| Oral                        | LD50          | >10,000 mg/kg (Rat)    |
| Dermal                      | LD50          | >10,000 mg/kg (Rabbit) |
| Inhalative                  | LC50/4 h      | >6.82 mg/l (Rat)       |
| 67-56-1 Methanol            |               |                        |
| Oral                        | LD50          | 1,187 mg/kg (Rat)      |
| Dermal                      | LD50          | 17,100 mg/kg (Rabbit)  |
| Inhalative                  | LC50/4 h      | 128.2 mg/l (Rat)       |
|                             | LC50/96 hours | 15,400 mg/l (Trout)    |

(Contd. on page 9)



|                                       |               |                     |
|---------------------------------------|---------------|---------------------|
| 14808-60-7 Quartz (SiO <sub>2</sub> ) |               |                     |
| Oral                                  | LD50          | >22,500 mg/kg (Rat) |
| Inhalative                            | LC50/96 hours | 1,033 mg/l (Trout)  |

• **Primary irritant effect:**

• **On the skin:**

Irritant to skin and mucous membranes.  
May cause an allergic skin reaction.

• **On the eye:** Irritating effect.

• **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

• **Carcinogenic categories:**

• **IARC (International Agency for Research on Cancer):**

"In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicate dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled"

(a) Although IARC has classified titanium dioxide as possible carcinogenic to human (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products which titanium dioxide is bound to other materials, such as in cosmetics or in paints."

(b) OSHA does not regulate Titanium Dioxide as a carcinogen. However, under 29 CFR 1910.1200 the SDS must convey the fact that Titanium Dioxide is a potential carcinogen to rats.

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to human

Group 4 - Probably not carcinogenic to humans

|            |                            |    |
|------------|----------------------------|----|
| 13463-67-7 | Titanium Dioxide           | 2B |
| 14808-60-7 | Quartz (SiO <sub>2</sub> ) | 1  |

• **NTP (National Toxicology Program):**

|            |                            |   |
|------------|----------------------------|---|
| 14808-60-7 | Quartz (SiO <sub>2</sub> ) | K |
|------------|----------------------------|---|

• **OSHA-Ca (Occupational Safety & Health Administration):**

|                                     |  |  |
|-------------------------------------|--|--|
| None of the ingredients are listed. |  |  |
|-------------------------------------|--|--|

## 12 Ecological Information

- **Toxicity:**
- **Aquatic toxicity:**  
Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.

|                                       |  |
|---------------------------------------|--|
| 68515-49-1 Diisodecyl Phthalate       |  |
| EC50                                  | 0.02 mg/l (Water flea)                             |
| 13463-67-7 Titanium Dioxide           |  |
| EC50                                  | >1,000 mg/l (Water flea)                           |
| 67-56-1 Methanol                      |  |
| EC50                                  | 22,000 mg/l (Green algae)<br>10,000 mg/l (Daphnia) |
| 14808-60-7 Quartz (SiO <sub>2</sub> ) |  |
| EC50                                  | 218 mg/l (Green algae)                             |

- **Persistence and degradability:** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**  
Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.  
Poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms
- **Results of PBT and vPvB assessment:**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

## 13 Disposal Considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Observe all federal, state and local environmental regulations when disposing of this material.
- **Uncleaned packaging**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport Information

- **UN-Number:**
- **DOT, ADR/ADN, ADN, IMDG, IATA** Non-Regulated Material
- **UN proper shipping name:**
- **DOT, ADR/ADN, ADN, IMDG, IATA** Non-Regulated Material
- **Transport hazard class(es):**
- **DOT, ADR/ADN, ADN, IMDG, IATA**
- **Class:** Non-Regulated Material

- **Packing group:** Non-Regulated Material
- **DOT, ADR/ADN, IMDG, IATA** Non-Regulated Material
- **Environmental hazards:** Not applicable.
- **Special precautions for user:** Not applicable.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.
- **UN "Model Regulation":** Non-Regulated Material

**15 Regulatory Information**

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

|  |  |
|--|--|
| · <b>Section 355 (extremely hazardous substances):</b> |  |
| None of the ingredients are listed.                    |  |

|  |          |
|--|----------|
| · <b>Section 313 (Specific toxic chemical listings):</b> |          |
| 67-56-1  | Methanol |

|   |   |
|---|---|
| · <b>TSCA (Toxic Substances Control Act):</b> |   |
| 471-34-1                                      | Calcium Carbonate                                 |
| 1317-65-3                                     | Natural limestone                                 |
| 68515-49-1                                    | Diisodecyl Phthalate                              |
| 57-11-4                                       | Stearic Acid, pure                                |
| 13463-67-7                                    | Titanium Dioxide                                  |
| 2768-02-7                                     | Trimethoxyvinylsilane                             |
| 67-56-1                                       | Methanol  |
| 1760-24-3                                     | N-(3-(trimethoxysilyl)propyl)ethylenediamine      |
| 52829-07-9                                    | Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate     |
| 25973-55-1                                    | 2-(2H-benzotriazol-2-yl)-4,6-di-tert-pentylphenol |
| 14808-60-7                                    | Quartz (SiO <sub>2</sub> )                        |

- **California Proposition 65:**  
Warning: This product contains a chemical known in the state of California to cause birth defects.

|   |                            |
|---|----------------------------|
| · <b>Chemicals known to cause cancer:</b> |                            |
| 13463-67-7                                | Titanium Dioxide           |
| 14808-60-7                                | Quartz (SiO <sub>2</sub> ) |

|  |  |
|--|--|
| · <b>Chemicals known to cause reproductive toxicity for females:</b> |  |
| None of the ingredients are listed.                                  |  |

|  |  |
|--|--|
| · <b>Chemicals known to cause reproductive toxicity for males:</b> |  |
| None of the ingredients are listed.                                |  |

|   |                      |
|---|----------------------|
| · <b>Chemicals known to cause developmental toxicity:</b> |                      |
| 68515-49-1  | Diisodecyl Phthalate |
| 67-56-1   | Methanol             |

|   |                            |
|---|----------------------------|
| · <b>New Jersey Right-to-Know List:</b> |                            |
| 1317-65-3                               | Natural limestone          |
| 13463-67-7                              | Titanium Dioxide           |
| 67-56-1                                 | Methanol                   |
| 14808-60-7                              | Quartz (SiO <sub>2</sub> ) |

|  |                            |        |
|--|----------------------------|--------|
| <ul style="list-style-type: none"> <li>• <b>New Jersey Special Hazardous Substance List:</b></li> </ul>                      |                            |        |
| 67-56-1  | Methanol                   | TE, F3 |
| 14808-60-7   | Quartz (SiO <sub>2</sub> ) | CA     |
| <ul style="list-style-type: none"> <li>• <b>Pennsylvania Right-to-Know List:</b></li> </ul>                                  |                            |        |
| 1317-65-3  | Natural limestone          |        |
| 13463-67-7   | Titanium Dioxide           |        |
| 14808-60-7   | Quartz (SiO <sub>2</sub> ) |        |
| <ul style="list-style-type: none"> <li>• <b>Pennsylvania Special Hazardous Substance List:</b></li> </ul>                    |                            |        |
| None of the ingredients are listed.  |                            |        |
| <ul style="list-style-type: none"> <li>• <b>Carcinogenic categories:</b></li> </ul>  |                            |        |
| <ul style="list-style-type: none"> <li>• <b>EPA (Environmental Protection Agency):</b></li> </ul>                            |                            |        |
| None of the ingredients are listed.  |                            |        |
| <ul style="list-style-type: none"> <li>• <b>TLV (Threshold Limit Value established by ACGIH):</b></li> </ul>                 |                            |        |
| 13463-67-7   | Titanium Dioxide           | A4     |
| 14808-60-7   | Quartz (SiO <sub>2</sub> ) | A2     |
| <ul style="list-style-type: none"> <li>• <b>NIOSH-Ca (National Institute for Occupational Safety and Health):</b></li> </ul> |                            |        |
| 13463-67-7   | Titanium Dioxide           |        |
| 14808-60-7   | Quartz (SiO <sub>2</sub> ) |        |

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms:**



GHS07    GHS08

- **Signal word:** Danger

- **Hazard-determining components of labeling:**

- Titanium Dioxide
- Dibutyltin bis(acetylacetonate)
- Quartz (SiO<sub>2</sub>)
- N-(3-(trimethoxysilyl)propyl)ethylenediamine

- **Hazard statements:**

- H320 Causes eye irritation.
- H317 May cause an allergic skin reaction.
- H350 May cause cancer.
- H360 May damage fertility or the unborn child.
- H401 Toxic to aquatic life.
- H412 Harmful to aquatic life with long lasting effects.

- **Precautionary statements:**

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P273 Avoid release to the environment.

|                |  |
|----------------|--|
| P280           | Wear protective gloves/protective clothing/eye protection/face protection.   |
| P302+P352      | If on skin: Wash with plenty of water.   |
| P305+P351+P338 | If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308+P313      | If exposed or concerned : Get medical advice/attention.  |
| P321           | Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).   |
| P333+P313      | If skin irritation or rash occurs: Get medical advice/ attention.  |
| P337+P313      | If eye irritation persists: Get medical advice/attention.  |
| P363           | Wash contaminated clothing before reuse.   |
| P405           | Store locked up.   |
| P501           | Dispose of contents/container in accordance with local/regional/national/international regulations.                              |

• **National regulations:**

None of the ingredients are listed.

• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

• **Date of preparation / last revision:** 05-03-2024

• **Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road  
 ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 NIOSH: National Institute for Occupational Safety and Health  
 OSHA: Occupational Safety & Health Administration  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 BEL: Biological Exposure Limit  
 Flam. Liq. 2: Flammable liquids – Category 2  
 Acute Tox. 3: Acute toxicity – Category 3  
 Acute Tox. 4: Acute toxicity – Category 4  
 Skin Corr. 1A: Skin corrosion/irritation – Category 1A  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
 Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B  
 Skin Sens. 1: Skin sensitisation – Category 1  
 Carc. 1A: Carcinogenicity – Category 1A  
 Carc. 2: Carcinogenicity – Category 2  
 Repr. 1B: Reproductive toxicity – Category 1B  
 STOT SE 1: Specific target organ toxicity (single exposure) – Category 1  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

(Contd. on page 14)

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2  
Aquatic Chronic 3: Hazardous to the aquatic environment - long- term aquatic hazard – Category 3